



SAFETY DATA SHEET

This safety data sheet complies with the requirements of: REACH Regulation (EC) No 1907/2006, as retained in UK law by (SI 2019/758 as amended)

IDENDEN 40-113 HIGH VELOCITY SOLVENTED DUCT SEALANT

Supersedes Date: 01-Sep-2022

Revision date 08-Aug-2023

Revision Number 1.08

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Name IDENDEN 40-113 HIGH VELOCITY SOLVENTED DUCT SEALANT

Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Sealant

Uses advised against None known

1.3. Details of the supplier of the safety data sheet

Company Name

Bostik Limited
Common Rd
ST16 3EH
Stafford UK
Tel: +44 (1785) 27 26 25
Fax: +44 (1785) 25 72 36

E-mail address SDS.box-EU@bostik.com

1.4. Emergency telephone number

United Kingdom Bostik: +44 (1785) 272650 (9am to 5pm Mon-Fri)
NHS: 111

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP (SI 2020/1567 as amended)

Skin corrosion/irritation	Category 2 - (H315)
Reproductive toxicity	Category 2 - (H361)
Specific target organ toxicity — single exposure	Category 3 - (H336)
Specific target organ toxicity — repeated exposure	Category 2 - (H373)
Chronic aquatic toxicity	Category 2 - (H411)
Flammable liquids	Category 2 - (H225)

2.2. Label elements

Contains Toluene, Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics, Acetone, Hydrocarbons, C6, isoalkanes, <5% n-hexane

SAFETY DATA SHEET

IDENTEN 40-113 HIGH VELOCITY SOLVENTED DUCT
SEALANT
Supersedes Date: 01-Sep-2022

Revision date 08-Aug-2023

Revision Number 1.08



Signal word
Danger

Hazard statements

H315 - Causes skin irritation.
H336 - May cause drowsiness or dizziness.
H361d - Suspected of damaging the unborn child.
H373 - May cause damage to organs through prolonged or repeated exposure.
H411 - Toxic to aquatic life with long lasting effects.
H225 - Highly flammable liquid and vapour.

EU Specific Hazard Statements

EUH208 - Contains Rosin & Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW. May produce an allergic reaction

Precautionary Statements - EU (§28, 1272/2008)

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
P260 - Do not breathe dust/fume/gas/mist/vapours/spray
P273 - Avoid release to the environment
P280 - Wear protective gloves/protective clothing/eye protection/face protection
P302 + P352 - IF ON SKIN: Wash with plenty of water and soap
P370 + P378 - In case of fire: Use dry chemical, CO₂, water spray or alcohol-resistant foam to extinguish
P391 - Collect spillage
P403 + P233 - Store in a well-ventilated place. Keep container tightly closed
P501 - Dispose of contents/ container to an approved waste disposal plant

Special provisions concerning the labelling of certain mixtures

Reserved for industrial and professional use.

Additional information

This product requires tactile warnings if supplied to the general public.

2.3. Other hazards

Harmful to aquatic life. In use, may form flammable/explosive vapour-air mixture.

PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Chemical name	EC No (EU Index No)	CAS No	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	REACH registration number
Toluene	(601-021-00-3)	108-88-3	10 - <20	Skin Irrit. 2 (H315)	-	01-2119471310-51-XXXX

SAFETY DATA SHEET

**IDENDEN 40-113 HIGH VELOCITY SOLVENTED DUCT
SEALANT**
Supersedes Date: 01-Sep-2022

Revision date 08-Aug-2023

Revision Number 1.08

	203-625-9			Repr. 2 (H361d) STOT SE 3 (H336) STOT RE 2 (H373) Asp. Tox. 1 (H304) Aquatic Chronic 3 (H412) Flam. Liq. 2 (H225)		
Precipitated nano calcium carbonate coated with calcium stearate	207-439-9	471-34-1	5 - <10	^	-	01-2119486795- 18-XXXX
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	927-510-4	RR-100219-3	5 - <10	STOT SE 3 (H336) Asp. Tox. 1 (H304) Skin Irrit. 2 (H315) Aquatic Chronic 2 (H411) Flam. Liq. 2 (H225)	-	01-2119475515- 33-xxxx
Acetone	(606-001-00- 8) 200-662-2	67-64-1	1 - <5	Eye Irrit. 2 (H319) (EUH066) STOT SE 3 (H336) Flam. Liq. 2 (H225)	-	01-2119471330- 49-XXXX
Hydrocarbons, C6, isoalkanes, <5% n-hexane	931-254-9	RR-100242-2	1 - <5	STOT SE 3 (H336) Asp. Tox. 1 (H304) Skin Irrit. 2 (H315) Aquatic Chronic 2 (H411) Flam Liq. 2 (H225) (EUH066)	-	01-2119484651- 34-XXXX
Zinc oxide	(030-013-00- 7) 215-222-5	1314-13-2	1 - <2.5	Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410)	-	01-2119463881- 32-XXXX
Bisphenol-A-Epichlorhyd rin Epoxy resin <= 700 MW	500-033-5	25068-38-6	0.1 - <0.5	Skin Irrit. 2 (H315) Eye Irrit. 2 (H319) Skin Sens. 1 (H317) Aquatic Chronic 2 (H411)	Eye Irrit. 2 :: C>=5% Skin Irrit. 2 :: C>=5%	01-2119456619- 26-xxxx
Rosin	(650-015-00- 7) 232-475-7	8050-09-7	0.1 - <0.3	Skin Sens. 1 (H317)	-	01-2119480418- 32-XXXX

Full text of H- and EUH-phrases: see section 16

SAFETY DATA SHEET

**IDENDEN 40-113 HIGH VELOCITY SOLVENTED DUCT
SEALANT**
Supersedes Date: 01-Sep-2022

Revision date 08-Aug-2023

Revision Number 1.08

Substances identified by a number starting "RR-" in the CAS-field are substances for which the CAS# is not adopted in EU and we use an internal numbering system to track within our SDS software

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

Notes

See section 16 for more information

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice	Show this safety data sheet to the doctor in attendance.
Inhalation	Remove to fresh air. IF exposed or concerned: Get medical advice/attention. Get medical attention immediately if symptoms occur.
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Do not rub affected area.
Skin contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Get medical attention if irritation develops and persists.
Ingestion	Do NOT induce vomiting. Rinse mouth. Never give anything by mouth to an unconscious person. Call a doctor.
Self-protection of the first aider	Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms	Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.
-----------------	---

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors	No information available.
------------------------	---------------------------

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable Extinguishing Media	Dry chemical. Carbon dioxide (CO ₂). Water spray. Alcohol resistant foam.
Unsuitable extinguishing media	No information available.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the chemical	Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Hazardous combustion products	Carbon oxides. Carbon monoxide. Carbon dioxide (CO ₂). Hydrocarbons. Hydrogen chloride. Zinc oxide.

SAFETY DATA SHEET

IDENDEN 40-113 HIGH VELOCITY SOLVENTED DUCT
SEALANT
Supersedes Date: 01-Sep-2022

Revision date 08-Aug-2023

Revision Number 1.08

5.3. Advice for firefighters

Special protective equipment and precautions for fire-fighters Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Evacuate personnel to safe areas. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Pay attention to flashback. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Do not touch or walk through spilled material.

Other information Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

For emergency responders Use personal protection recommended in Section 8.

6.2. Environmental precautions

Environmental precautions Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or spillage if safe to do so. Prevent product from entering drains.

6.3. Methods and material for containment and cleaning up

Methods for containment Stop leak if you can do it without risk. Do not touch or walk through spilled material. A vapour suppressing foam may be used to reduce vapours. Dyke far ahead of spill to collect run-off water. Keep out of drains, sewers, ditches and waterways. Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal.

Methods for cleaning up Take precautionary measures against static discharges. Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labelled containers.

Prevention of secondary hazards Eliminate all ignition sources if safe to do so.

6.4. Reference to other sections

Reference to other sections See section 8 for more information. See section 13 for more information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling Use personal protection equipment. Avoid breathing vapours or mists. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use with local exhaust ventilation. Use spark-proof tools and explosion-proof equipment. Keep in an area equipped with sprinklers. Use according to package label instructions. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Remove contaminated clothing and shoes. Take off contaminated clothing and wash it before reuse. In case of insufficient ventilation, wear suitable respiratory equipment.

General hygiene considerations Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the

SAFETY DATA SHEET

IDENTEN 40-113 HIGH VELOCITY SOLVENTED DUCT
SEALANT
Supersedes Date: 01-Sep-2022

Revision date 08-Aug-2023

Revision Number 1.08

product. Wear suitable gloves and eye/face protection.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labelled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations. Store locked up.

Recommended storage temperature

Keep at temperatures between 5 and 25 °C.

7.3. Specific end use(s)

Specific use(s)

Sealant.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Other information

Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure Limits

Chemical name	European Union	United Kingdom
Toluene 108-88-3	TWA: 50 ppm TWA: 192 mg/m ³ *	TWA: 50 ppm TWA: 191 mg/m ³ STEL: 100 ppm STEL: 384 mg/m ³ Sk*
Limestone 1317-65-3	-	TWA: 10 mg/m ³ TWA: 4 mg/m ³ STEL: 30 mg/m ³ STEL: 12 mg/m ³
Aluminum hydroxide (Al(OH) ₃) 21645-51-2	-	TWA: 10 mg/m ³ TWA: 4 mg/m ³ STEL: 30 mg/m ³ STEL: 12 mg/m ³
Acetone 67-64-1	TWA: 500 ppm TWA: 1210 mg/m ³	TWA: 500 ppm TWA: 1210 mg/m ³ STEL: 1500 ppm STEL: 3620 mg/m ³
Rosin 8050-09-7	-	TWA: 0.05 mg/m ³ STEL: 0.15 mg/m ³ Sen+

Chemical name	European Union	Ireland	United Kingdom
Toluene 108-88-3	-	0.02 mg/L (blood - Toluene prior to last shift of workweek) 0.03 mg/L (urine - Toluene end of shift) 0.3 mg/g Creatinine (urine - o-Cresol end of shift)	-
Acetone 67-64-1	-	50 mg/L (urine - Acetone end of shift)	-

Derived No Effect Level (DNEL) No information available

SAFETY DATA SHEET

**IDENDEN 40-113 HIGH VELOCITY SOLVENTED DUCT
SEALANT**
Supersedes Date: 01-Sep-2022

Revision date 08-Aug-2023

Revision Number 1.08

Derived No Effect Level (DNEL)			
Toluene (108-88-3)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Long term Systemic health effects worker	Dermal	384 mg/kg bw/d	
Long term Systemic health effects Local health effects worker	Inhalation	192 mg/m ³	
Short term Systemic health effects worker	Inhalation	384 mg/m ³	
Long term Local health effects worker	Inhalation	192 mg/m ³	
Short term Local health effects	Inhalation	384 mg/m ³	

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (RR-100219-3)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Long term Systemic health effects worker	Inhalation	2085 mg/m ³	
Long term Systemic health effects	Dermal	300 mg/kg bw/d	

Acetone (67-64-1)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Long term Systemic health effects worker	Dermal	186 mg/kg bw/d	
Short term Local health effects worker	Inhalation	2420 mg/m ³	
Long term Systemic health effects worker	Inhalation	1210 mg/m ³	

Zinc oxide (1314-13-2)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Long term Systemic health effects worker	Inhalation	5 mg/m ³	
Long term Local health effects worker	Inhalation	0.5 mg/m ³	
Long term Systemic health effects	Dermal	83 mg/kg bw/d	

Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW (25068-38-6)			
Type	Exposure route	Derived No Effect Level	Safety factor

SAFETY DATA SHEET

**IDENDEN 40-113 HIGH VELOCITY SOLVENTED DUCT
SEALANT**
Supersedes Date: 01-Sep-2022

Revision date 08-Aug-2023

Revision Number 1.08

		(DNEL)	
worker Short term Systemic health effects	Dermal	8.33 mg/kg bw/d	
worker Long term Systemic health effects	Dermal	8.33 mg/kg bw/d	
worker Short term Systemic health effects	Inhalation	12.25 mg/kg bw/d	

Rosin (8050-09-7)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Local health effects	Inhalation	10 mg/m ³	
worker Long term Systemic health effects	Dermal	2131 mg/kg bw/d	

Derived No Effect Level (DNEL)			
Toluene (108-88-3)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Inhalation	56.5 mg/m ³	
Consumer Short term Systemic health effects	Inhalation	226 mg/m ³	
Consumer Long term Local health effects	Inhalation	56 mg/m ³	
Consumer Local health effects Short term	Inhalation	226 mg/m ³	
Consumer Long term Systemic health effects	Dermal	226 mg/kg bw/d	
Consumer Long term Systemic health effects	Oral	8.13 mg/kg bw/d	

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (RR-100219-3)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Inhalation	447 mg/m ³	
Consumer Long term Systemic health effects	Dermal	149 mg/kg bw/d	
Consumer Long term Systemic health effects	Oral	149 mg/kg bw/d	

Acetone (67-64-1)			
--------------------------	--	--	--

SAFETY DATA SHEET

**IDENDEN 40-113 HIGH VELOCITY SOLVENTED DUCT
SEALANT**
Supersedes Date: 01-Sep-2022

Revision date 08-Aug-2023

Revision Number 1.08

Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Inhalation	200 mg/m ³	
Consumer Long term Systemic health effects	Dermal	62 mg/kg bw/d	
Consumer Long term Systemic health effects	Oral	62 mg/kg bw/d	

Zinc oxide (1314-13-2)

Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Inhalation	2.5 mg/m ³	
Consumer Long term Systemic health effects	Dermal	83 mg/kg bw/d	
Consumer Long term Systemic health effects	Oral	0.83 mg/kg bw/d	

Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW (25068-38-6)

Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Short term Systemic health effects	Dermal	3.571 mg/kg bw/d	
Consumer Short term Systemic health effects	Oral	0.75 mg/kg bw/d	
Consumer Long term Systemic health effects	Dermal	3.571 mg/kg bw/d	
Consumer Long term Systemic health effects	Oral	0.75 mg/kg bw/d	

Rosin (8050-09-7)

Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Dermal	1065 mg/kg bw/d	
Consumer Long term Systemic health effects	Oral	1065 mg/kg bw/d	

Predicted No Effect Concentration (PNEC)

Predicted No Effect Concentration (PNEC)

Toluene (108-88-3)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.68 mg/l
Marine water	0.68 mg/l

SAFETY DATA SHEET

IDENDEN 40-113 HIGH VELOCITY SOLVENTED DUCT SEALANT
Supersedes Date: 01-Sep-2022

Revision date 08-Aug-2023

Revision Number 1.08

Sewage treatment plant	13.61 mg/l
Freshwater sediment	16.39 mg/kg dry weight
Marine sediment	16.39 mg/kg dry weight
Soil	2.89 mg/kg dry weight

Acetone (67-64-1)

Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	10.6 mg/l
Freshwater - intermittent	21 mg/l
Marine water	1.06 mg/l
Microorganisms in sewage treatment	100 mg/l
Freshwater sediment	30.4 mg/kg dry weight
Marine water	3.04 mg/kg dry weight
Soil	29.5 mg/kg dry weight

Zinc oxide (1314-13-2)

Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.0206 mg/l
Marine water	0.0061 mg/l
Freshwater sediment	235.6 mg/kg dry weight
Marine sediment	113 mg/kg dry weight
Soil	106.8 mg/kg dry weight
Microorganisms in sewage treatment	0.1 mg/l

Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW (25068-38-6)

Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.006 mg/l
Marine water	0.0006 mg/l
Freshwater sediment	0.996 mg/l
Marine sediment	0.0996 mg/l
Soil	0.196 mg/l

Rosin (8050-09-7)

Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.002 mg/l
Marine water	0 mg/l
Sewage treatment plant	1000 mg/l
Freshwater sediment	0.007 mg/l
Marine sediment	0.001 mg/l

8.2. Exposure controls

Engineering controls

Ensure adequate ventilation, especially in confined areas. Vapours/aerosols must be exhausted directly at the point of origin.

Personal protective equipment

Eye/face protection

Tight sealing safety goggles. Face protection shield. Eye protection must conform to standard EN 166.

Hand protection

Wear protective gloves. Gloves must conform to standard EN 374. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. The breakthrough time of the gloves depends on the material and the thickness as well as the temperature. Gloves should be replaced regularly and if there is any sign of damage to the glove material.

Skin and body protection

Antistatic footwear. Wear fire/flammable resistant/retardant clothing. Suitable protective clothing.

Respiratory protection

In case of inadequate ventilation wear respiratory protection. In case of mist, spray or aerosol exposure wear suitable personal respiratory protection and protective suit.

Recommended filter type:

Organic gases and vapours filter conforming to EN 14387.

Environmental exposure controls

Do not allow into any sewer, on the ground or into any body of water.

SAFETY DATA SHEET

IDENTEN 40-113 HIGH VELOCITY SOLVENTED DUCT
SEALANT
Supersedes Date: 01-Sep-2022

Revision date 08-Aug-2023

Revision Number 1.08

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid	
Appearance	Paste	
Colour	Grey	
Odour	Characteristic.	
Property	Values	Remarks • Method
Melting point / freezing point	No data available	None known
Initial boiling point and boiling range	> 48 °C	
Flammability	Not applicable for liquids .	
Flammability Limit in Air		None known
Upper flammability or explosive limits	No data available	
Lower flammability or explosive limits	No data available	
Flash point	-30 °C	
Autoignition temperature	No data available	None known
Decomposition temperature		None known
pH	No data available	Not applicable. Insoluble in water.
pH (as aqueous solution)	No data available	None known
Kinematic viscosity	> 700 mm ² /s	None known
Dynamic viscosity	No data available	
Water solubility	No data available.	None known
Solubility(ies)	No data available	None known
Partition coefficient	No data available	None known
Vapour pressure	No data available	None known
Relative density	No data available	None known
Bulk Density	No data available	
Density	1.3 g/cm ³	
Relative vapour density	No data available	None known
Particle characteristics		
Particle Size	No information available	
Particle Size Distribution	No information available	

9.2. Other information

Solid content (%)	No information available	
VOC content	>= 408 g/L	European directive n°2010/75/UE

9.2.1. Information with regards to physical hazard classes
Not applicable

9.2.2. Other safety characteristics
No information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity No information available.

10.2. Chemical stability

Stability Stable under normal conditions.

Explosion data

SAFETY DATA SHEET

IDENTEN 40-113 HIGH VELOCITY SOLVENTED DUCT
SEALANT
Supersedes Date: 01-Sep-2022

Revision date 08-Aug-2023

Revision Number 1.08

Sensitivity to mechanical impact None.
Sensitivity to static discharge Yes.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

Conditions to avoid Heat, flames and sparks.

10.5. Incompatible materials

Incompatible materials Strong acids. Strong bases. Strong oxidising agents.

10.6. Hazardous decomposition products

Hazardous decomposition products None under normal use conditions. Carbon oxides. Hydrogen chloride.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure

Product Information

Inhalation	Specific test data for the substance or mixture is not available. May cause irritation of respiratory tract. May cause drowsiness or dizziness.
Eye contact	Based on available data, the classification criteria are not met.
Skin contact	Specific test data for the substance or mixture is not available. Causes skin irritation. (based on components).
Ingestion	Specific test data for the substance or mixture is not available. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Redness. May cause redness and tearing of the eyes. Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Acute toxicity

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)	92,766.20 mg/kg
ATEmix (dermal)	>5000 mg/kg
ATEmix (inhalation-gas)	>20000 ppm
ATEmix (inhalation-dust/mist)	>5 mg/l
ATEmix (inhalation-vapour)	>20 mg/l

Component Information

SAFETY DATA SHEET

IDENDEN 40-113 HIGH VELOCITY SOLVENTED DUCT SEALANT
Supersedes Date: 01-Sep-2022

Revision date 08-Aug-2023

Revision Number 1.08

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Toluene	=5580 mg/kg (Rattus)	= 12000 mg/kg (Oryctolagus cuniculus)	>20 mg/L (Rattus) 4 h
Precipitated nano calcium carbonate coated with calcium stearate	= 6450 mg/kg (Rat)	> 2000 mg/kg (Rat)	> 3 mg/L (Rat) 4 h
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	LD50 >5840 mg/kg Rat	LD50 >2920 mg/kg (Rattus)	LC50 >23.3 mg/L (4h)(Rat, vapour) (OECD 403)
Acetone	=5800 mg/kg (Rattus) 3000 mg/Kg (mouse)	>15800 mg/Kg (Rattus)	=79 mg/l(Rattus) 4 h
Hydrocarbons, C6, isoalkanes, <5% n-hexane	>16750 mg/Kg (Rattus)	>3350 mg/Kg (Oryctolagus cuniculus) OECD 402	259354 mg/m ³ (vapour) (rat OECD 403)
Zinc oxide	>5000 mg/kg (Rattus)	LD50 >2000 mg/Kg (Rattus) (OECD 402)	LC50 (4h) >5.7 mg/l
Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW	LD50 (Rattus) > 2000 mg/kg OECD 420	>2000 mg/Kg (Rattus)	-
Rosin	>2000 mg/Kg (Rattus)	> 2500 mg/kg (Oryctolagus cuniculus)	=1.5 mg/L (Rattus) 4 h

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation

Classification based on data available for ingredients. Causes skin irritation.

Toluene (108-88-3)

Method	Species	Exposure route	Effective dose	Exposure time	Results
Regulation (EC) No. 440/2008, Annex, B.4	Rabbit	Dermal			Irritant

Serious eye damage/eye irritation Based on available data, the classification criteria are not met.

Acetone (67-64-1)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405: Acute Eye Irritation/Corrosion	Rabbit	eye			irritant

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

Toluene (108-88-3)

Method	Species	Exposure route	Results
Regulation (EC) No. 440/2008, Annex, B.6 (Maximisation test)	Guinea pig		No sensitisation responses were observed

Acetone (67-64-1)

Method	Species	Exposure route	Results
OECD Test No. 406: Skin Sensitisation	Guinea pig	Dermal	Not a skin sensitizer

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Component Information

Toluene (108-88-3)

Method	Species	Results
Regulation (EC) No. 440/2008, Annex, B.13/14 (Ames test)	Salmonella typhimurium	Not mutagenic

SAFETY DATA SHEET

IDENTEN 40-113 HIGH VELOCITY SOLVENTED DUCT
SEALANT
Supersedes Date: 01-Sep-2022

Revision date 08-Aug-2023

Revision Number 1.08

OECD Test No. 476: In vitro Mammalian Cell Gene Mutation Test	Mouse	Not mutagenic
---	-------	---------------

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Contains a known or suspected reproductive toxin. Classification based on data available for ingredients. Suspected of damaging fertility or the unborn child.

The table below indicates ingredients above the cut-off threshold considered as relevant which are listed as reproductive toxins.

Chemical name	European Union
Toluene	Repr. 2

Toluene (108-88-3)

Method	Species	Results
OECD 407	in vivo	reproductive toxicant

STOT - single exposure May cause drowsiness or dizziness.

STOT - repeated exposure May cause damage to organs through prolonged or repeated exposure.

Toluene (108-88-3)

Method	Species	Exposure route	Effective dose	Exposure time	Results
Regulation (EC) No. 440/2008, Annex, B.26	Rat, male, female	Oral		91 days	NOAEL: 625 mg/kg
OECD Test No. 453: Combined Chronic Toxicity/Carcinogenicity Studies	Rat, male, female	Inhalation, vapour			NOAEL: 1.131 mg/l

Aspiration hazard Based on available data, the classification criteria are not met.

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

Endocrine disrupting properties

11.2.2. Other information

Other adverse effects No information available.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity Toxic to aquatic life with long lasting effects. Harmful to aquatic life.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
Toluene 108-88-3	EC50 72 h = 12.5 mg/L	LC50 96 h 5.89 - 7.81 mg/L	EC50 = 19.7 mg/L 30 min	EC50: =11.5mg/L (48h,		

SAFETY DATA SHEET

IDENDEN 40-113 HIGH VELOCITY SOLVENTED DUCT SEALANT
Supersedes Date: 01-Sep-2022

Revision date 08-Aug-2023

Revision Number 1.08

	(Pseudokirchneriella subcapitata)	(Oncorhynchus mykiss flow-through) LC50 96 h = 5.8 mg/L (Oncorhynchus mykiss semi-static)		Daphnia magna) EC50: 5.46 - 9.83mg/L (48h, Daphnia magna)		
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics RR-100219-3	ErL50 (72h) = 10-30 mg/L (Pseudokirchneriella subcapitata)	LL50 (96h) >13.4 mg/L (Oncorhynchus mykiss) OECD 203	-	EL50 (48h) = 3.0 mg/L (Daphnia magna)		
Acetone 67-64-1	-	LC50 96 h 4.74 - 6.33 mL/L (Oncorhynchus mykiss)	EC50 = 14500 mg/L 15 min	EC50 48 h 10294 - 17704 mg/L (Daphnia magna Static)		
Hydrocarbons, C6, isoalkanes, <5% n-hexane RR-100242-2	EL50 (72h) = 13.6 mg/l (Pseudokirchneriella subcapitata)	LL50 (96h) = 18.27 mg/l (Oncorhynchus mykiss)	-	EL50 (48h)= 31.9 mg/l (Daphnia magna)		
Zinc oxide 1314-13-2	LC 50 (72Hr) 0.136 mg/L	LC50 (96h) =0.7 mg/L (Danio rerio)	-	LC 50 (48Hr) =0.5 mg/l (Ceriodaphnia dubia)	1	1
Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW 25068-38-6	EC50 (72h) = 9.4 mg/L (Scenedesmus capricornutum) EPA-660/3-75-009	1.2 mg/l 96Hr (Oncorhynchus mykiss)	-	2.7 mg/l 48hr Daphia Magna		
Rosin 8050-09-7	EC50: =400mg/L (72h, Desmodemus subspicatus)	LC50 (96h) >10mg/L (Danio rerio)	EC50 = 31.5 mg/L 30 min	EC50 48 h >100 mg/L (Daphnia magna)		

12.2. Persistence and degradability

Persistence and degradability No information available.

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (RR-100219-3)

Method	Exposure time	Value	Results
OECD Test No. 301F: Ready Biodegradability: Manometric Respirometry Test (TG 301 F)	28 days	98%	Readily biodegradable

Acetone (67-64-1)

Method	Exposure time	Value	Results
OECD Test No. 301B: Ready Biodegradability: CO2 Evolution Test (TG 301 B)	28 days	biodegradation	91 % Readily biodegradable

Zinc oxide (1314-13-2)

Method	Exposure time	Value	Results
			The methods for determining biodegradability are not applicable to inorganic substances

12.3. Bioaccumulative potential

SAFETY DATA SHEET

IDENTEN 40-113 HIGH VELOCITY SOLVENTED DUCT
SEALANT
Supersedes Date: 01-Sep-2022

Revision date 08-Aug-2023

Revision Number 1.08

Bioaccumulation

Component Information

Chemical name	Partition coefficient
Toluene	3.93
Acetone	-0.24
Hydrocarbons, C6, isoalkanes, <5% n-hexane	3.6
Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW	3.26
Rosin	7.7

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment The product does not contain any substance(s) classified as PBT or vPvB above the threshold of declaration.

Chemical name	PBT and vPvB assessment
Toluene	The substance is not PBT / vPvB PBT assessment does not apply
Precipitated nano calcium carbonate coated with calcium stearate	The substance is not PBT / vPvB PBT assessment does not apply
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	The substance is not PBT / vPvB
Acetone	The substance is not PBT / vPvB PBT assessment does not apply
Hydrocarbons, C6, isoalkanes, <5% n-hexane	The substance is not PBT / vPvB
Zinc oxide	The substance is not PBT / vPvB PBT assessment does not apply
Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW	The substance is not PBT / vPvB
Rosin	The substance is not PBT / vPvB Further information relevant for the PBT assessment is necessary

12.6. Endocrine disrupting properties

Endocrine disrupting properties No information available.

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused products Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

Contaminated packaging Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers.

Waste codes / waste designations according to EWC 15 01 10*: Packaging containing residues of or contaminated by dangerous substances. 16 03 03* inorganic wastes containing hazardous substances. 16 05 05 gases in pressure containers other than those mentioned in 16 05 04. Waste codes should be assigned by the user based on the application for which the product was used.

SAFETY DATA SHEET

IDENDEN 40-113 HIGH VELOCITY SOLVENTED DUCT
SEALANT
Supersedes Date: 01-Sep-2022

Revision date 08-Aug-2023

Revision Number 1.08

European Waste Catalogue	08 04 09* waste adhesives and sealants containing organic solvents or other dangerous substances 15 01 10*: Packaging containing residues of or contaminated by dangerous substances
Other information	Waste codes should be assigned by the user based on the application for which the product was used.

SECTION 14: Transport information

Note: The information shown here, may not always agree with the bill of lading shipping description for the material. The shipping descriptions shown here are for bulk shipments only, and may not apply to shipments made in non-bulk packages (see regulatory definition).

Land transport (ADR/RID)

14.1 UN number or ID number	UN1133
14.2 UN proper shipping name	Adhesives
14.3 Transport hazard class(es)	3
Labels	3
14.4 Packing group	II
Description	UN1133, Adhesives, 3, II, (D/E), Environmentally Hazardous
14.5 Environmental hazards	Yes
14.6 Special precautions for user	
Special Provisions	640D
Classification code	F1
Tunnel restriction code	(D/E)
Limited quantity (LQ)	5 L
ADR Hazard Id (Kemmler Number)	33

IMDG

14.1 UN number or ID number	UN1133
14.2 UN proper shipping name	Adhesives
14.3 Transport hazard class(es)	3
14.4 Packing group	II
Description	UN1133, Adhesives, 3, II, (-30°C c.c.), Marine Pollutant
14.5 Marine pollutant	P
14.6 Special precautions for user	
Special Provisions	None
Limited Quantity (LQ)	5 L
EmS-No.	F-E, S-D
14.7 Maritime transport in bulk according to IMO instruments	
Transport in bulk according to Annex II of MARPOL and the IBC Code	Not applicable

Air transport (ICAO-TI / IATA-DGR)

14.1 UN number or ID number	UN1133
14.2 UN proper shipping name	Adhesives
14.3 Transport hazard class(es)	3
14.4 Packing group	II
Description	UN1133, Adhesives, 3, II
14.5 Environmental hazards	Yes
14.6 Special precautions for user	
Special Provisions	A3
Limited quantity (LQ)	1 L
ERG Code	3L

Section 15: REGULATORY INFORMATION

SAFETY DATA SHEET

IDENTEN 40-113 HIGH VELOCITY SOLVENTED DUCT
SEALANT
Supersedes Date: 01-Sep-2022

Revision date 08-Aug-2023

Revision Number 1.08

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product contains one or more substance(s) subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Chemical name	CAS No	Restricted substance per REACH Annex XVII
Toluene	108-88-3	48.
Precipitated nano calcium carbonate coated with calcium stearate	471-34-1	75.

48 . Reserved for industrial and professional use. Adhesives or spray paint shall not be placed on the market containing above substance equal to or greater than 0.1% where supplied to the general public.

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Dangerous substance category per Seveso Directive (2012/18/EU)

P5a - FLAMMABLE LIQUIDS

P5b - FLAMMABLE LIQUIDS

P5c - FLAMMABLE LIQUIDS

E2 - Hazardous to the Aquatic Environment in Category Chronic 2

Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

Persistent Organic Pollutants

Not applicable

REGULATION (EU) 2019/1148 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 20 June 2019 on the marketing and use of explosives precursors

This product contains

Chemical name	Reporting of suspicious transactions, disappearances and thefts	Restricted
Acetone - 67-64-1	X	

SAFETY DATA SHEET

IDENTEN 40-113 HIGH VELOCITY SOLVENTED DUCT
SEALANT
Supersedes Date: 01-Sep-2022

Revision date 08-Aug-2023

Revision Number 1.08

National regulations

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of H-Statements referred to under section 3

EUH066 - Repeated exposure may cause skin dryness or cracking
H225 - Highly flammable liquid and vapour
H304 - May be fatal if swallowed and enters airways
H315 - Causes skin irritation
H317 - May cause an allergic skin reaction
H319 - Causes serious eye irritation
H336 - May cause drowsiness or dizziness
H361d - Suspected of damaging the unborn child
H373 - May cause damage to organs through prolonged or repeated exposure
H400 - Very toxic to aquatic life
H410 - Very toxic to aquatic life with long lasting effects
H411 - Toxic to aquatic life with long lasting effects
H412 - Harmful to aquatic life with long lasting effects

Legend

TWA	TWA (time-weighted average)
STEL	STEL (Short Term Exposure Limit)
Ceiling	Ceiling Limit Value
*	Skin designation
SVHC	Substance(s) of Very High Concern
PBT	Persistent, Bioaccumulative, and Toxic (PBT) Chemicals
vPvB	Very Persistent and very Bioaccumulative (vPvB) Chemicals
STOT RE	Specific target organ toxicity - Repeated exposure
STOT SE	Specific target organ toxicity - Single exposure
EWC	European Waste Catalogue
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
IMDG	International Maritime Dangerous Goods (IMDG)
IATA	International Air Transport Association (IATA)
RID	Regulations concerning the International Transport of Dangerous Goods by Rail

Key literature references and sources for data

No information available

Prepared By Product Safety & Regulatory Affairs
Revision date 08-Aug-2023

Indication of changes

Revision note SDS sections updated, 2, 3, 5, 6, 7, 8, 15.
Training Advice Provide adequate information, instruction, and training for operator
Further information No information available

This material safety data sheet complies with requirements of UK REACH Regulations (SI 2019/758 as amended)

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of

SAFETY DATA SHEET

**IDENDEN 40-113 HIGH VELOCITY SOLVENTED DUCT
SEALANT**

Supersedes Date: 01-Sep-2022

Revision date 08-Aug-2023

Revision Number 1.08

its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet