







MAX Hi-Flow

CONDENSATE REMOVAL PUMP

The best in class Max Hi-Flow tank pump carries on the Aspen Pumps tradition of build quality & high performance. With the lowest dB(A) rating & best IP rating (IP24 splash proof) of any tank pump, the Max Hi-Flow is the guietest & safest pump in its class.



550 L/h max. flow



5m max. rec. head (flow rate 55L/h)

KEY FEATURES


- IP24 Splash proof
- Easy access tank
- Built in spirit level
- Plug & play


SUITABILITY

- Up to 733kW / 2.5m Btu/h
- Ducted units; Floor standing
- & Chassis units; Cassette units



FP3349








TANK PUMP SPECIFICATIONS	
Max. flow	550L/h @ 0 head
Max. rec. head	5m
Tank capacity	1.7L
Sound level@1m	44 dB(A)
Power supply	230 VAC, 0.8A, 50Hz
Rated	Non Continuous
Class	I appliance
Max. unit output	733kW / 2.5m Btu/h

Max. water temp 40°C / 104°F Inlets x4 21-27mm Outlets 6mm & 10mm **IP Protection** IP24 Safety switch 3A Normally closed Thermal protection Fully potted n/a

10mm flow 5m max. recommended head METRES HEAD 3 2 230 VAC 0 300 500 LITRES PER HOUR



SUGGESTED XTRA ACCESSORIES Description Part No. Rubber adaptor FP2013 Rigid pipe B7501 15mm / 3/4" FP2038 Hose to waste



MAX Hi-Flow

For more installation accessories take a look at our Aspen Xtra range

IN THE BOX

Max Hi-Flow tank pump • Plug & Play power cable • Fixing kit incl. rod mount and wall mount clips • Install manual

Download manual at aspenpumps.com View install video at aspenpumps.com

Information correct at time of going to press



Self priming





n/a



