



Spiral Access Doors

Description

- Double skin construction.
- Manufactured from 0.8mm galvanised mild steel (as standard).
- 6mm closed cell polyethylene gasket to the inner panel sealing the duct internally.
- A positive seal is achieved via 2 external thermo plastic, tri-star threaded (m10) hand wheels, tightened onto press fitted internal fully threaded (m10) set bolts. (Zinc plated mild steel).
- Set bolt ends are pressed to purposely detect the thread ends, not allowing the access door to be completely disassembled, reducing the risk of the inner panel separating.
- Conical stainless steel springs fitted between the inner and outer panel offers a sprung separation for ease of installation and removal.

Material Options

- Galvanised Mild Steel (Stocked).
- 304 Stainless Steel (Special order).
- 316 Stainless Steel (Special order).

Available Options (Special Order)

- Rubber -Safe edging strip.
- Factory fitted safety retaining chain.

Installation Instructions

Self adhesive disposable duct hole cut out template, complete with installation instructions packaged with each access door.

Standard Stocked Sizes	
Overall Door Size W (mm) x H (mm)	To Suit Duct Diameter (mm)
200 x 80	100
200 x 80	125
250 x 150	150
250 x 150	160
250 x 150	180
250 x 150	200
250 x 150	224
250 x 150	250
250 x 150	280
250 x 150	300
250 x 150	315
250 x 150	355
250 x 150	400
250 x 150	450
400 x 300	500
400 x 300	560
400 x 300	630
400 x 300	711
400 x 300	762
400 x 300	813