



## Square / Rectangular Access Doors (with chain)

### Description

- Easy to install.
- Double skinned construction.
- Manufactured from 0.8mm galvanised mild steel (as standard).
- Encapsulating 25mm 60 kg/m<sup>2</sup> Rockwool Insulation.
- 6mm closed cell polyethylene gasket adhered to both inner & outer sub-frame, reducing the risk of air leakage.
- A positive seal is achieved via 1.2mm progressive action cam lock fasteners.
- Radius knock-over tabs, reducing the risk of personal injury when handling.
- Factory fitted safety retaining chain (welded oval link, bright zinc plated mild steel) attached to both door panel & sub-frame.
- Certification - BSRIA Approved Quality Pressure Tested

### Door Depth Options.

- 25mm Deep.
- 50mm Deep (Special Order).

### Fire Retardant Options (Special Order)

- Encapsulating 25mm 128kg Ceramic Blanket Insulation
- 6mm (FMVSS 302) PVC Gasket adhered to both inner & outer sub-frame.

### Material Options

- Galvanised Mild Steel (Stocked)
- 304 Stainless Steel (Special Order).
- 316 Stainless Steel (Special Order).



Door & Frame Overall Size W (mm) x H (mm)	Required Duct Opening Size W (mm) x H (mm)
*100 x 100	60 x 60
150 x 100	110 x 60
*150 x 150	110 x 110
200 x 100	160 x 60
200 x 150	160 x 110
*200 x 200	160 x 160
250 x 150	210 x 110
250 x 200	210 x 160
*250 x 250	210 x 210
*300 x 150	260 x 110
*300 x 200	260 x 160
*300 x 300	260 x 260
*400 x 200	360 x 160
400 x 300	360 x 260
*400 x 400	360 x 360
450 x 300	410 x 260
*450 x 450	410 x 410
*500 x 500	460 x 460
600 x 300	560 x 260
600 x 400	560 x 360
600 x 450	560 x 410
*600 x 600	560 x 560
* Standard Stock Sizes	